

LIFEBOOK S6410

Get ready for your next business trip

Issue December 2007

Pages 4

The exclusive LIFEBOOK S6410 is your best friend on the move, leaving no compromises!

The sturdy notebook keeps the balance between low weight, best connectivity, high-end performance and modularity. With its integrated UMTS/HSUPA, ConfCamera and brilliant 13.3-inch wide display, you are going to experience true mobility – anywhere, anytime.

The combination of performance, modularity and flexibility gives you the functionality and ease of use of a full-sized PC. Intel® Centrino® Duo Mobile Technology with latest Intel® GM965 chipset technology delivers high performance and Business-day-long independency from the power socket.

This notebook is designed for highest quality with extensive testing and an extra-strong magnesium lid.

Elegance

Designed for the most demanding mobile users, LIFEBOOKs are the perfect synthesis of form, function and style.

- Light-weight modular 13.3-inch wide notebook with only 1.7 kg
- Exclusive protective leather bag
- Modular bay fitting an optical disk drive or battery
- Excellent resolution and video quality

Ergonomics

- 13.3-inch WXGA -display for maximum viewing comfort
- Convenient working with full sized keyboard
- Small in size but great expandability with maximum ports
- Eco Button to extend battery life by powering down energy consumption

Connectivity

- Bluetooth and Wireless LAN optional integrated
- Optional Port Replicator for easy connection to all your peripherals, compatible with LIFEBOOK E Series and LIFEBOOK C Series
- Long lasting battery for Business-day long independency with first and second battery

Security

- Trusted platform module (TPM 1.2) provides more secure applications and makes transitions safe
- Biometric fingerprint sensor
- Built-in SmartCard controller and optional SmartCase Logon+: software with best integration into your IT environment
- Lock workstation Button for fast sign off the system

Reliability

- Highest quality design with magnesium lid
- Hard disk drive ShockSensor minimizes data loss and guarantees a higher reliability of your data
- Spill-proof keyboard offers protection against system damage

Manageability

- Integrate the bundled system management software Desk View Admin in every common IT infrastructure
- Seamless integration in heterogeneous enterprise management systems
- Get optional add on packages: With DeskView Migrate and DeskView Control for e.g. migration projects and extensive client lifecycle management tasks



System		LIFEBOOK S6410
Processor		
Intel® Core™2 Duo Processor		T7100 (1.8GHz)
Second level cache		2 MB
Front side bus (FSB)		800 MHz
Intel® Core™2 Duo Processor		
Second level cache		T7300 (2.0GHz)
Front side bus (FSB)		T7500 (2.2GHz)
		T7700 (2.4GHz)*
		4 MB
		800MHz
Chipset		
Northbridge		Intel® GM965
Southbridge		ICH 8-M
Memory		
DIMM slots	2	
DDR2-667 SDRAM, 667 MHz		up to 4GB
BIOS		
BIOS Flash EPROM	BIOS based on Phoenix TrustedCore Notebook	
Interfaces		
SIM card slot		1
Infrared link (Fast IrDa 1.1, 4 Mbps)		1
Type I/II PC Card slot		1
Memory card slot (SD, MS, xD and MPRO)		1
USB 2.0		3
S-Video out (TV-out) without adapter cable		1
VGA		1
Modem RJ-11		1
LAN RJ-45		1
Audio-in (line-in / microphone)		1
Audio-out (line-out / headphone)		1
DC-in		1
IEEE1394		1
Kensington Lock		1
Docking connector for Port Replicator		1
Port Replicator interfaces (optional):		
USB 2.0		4
VGA		1
DVI-D		1
Serial port		(with HDCP support)
Parallel port		1
LAN RJ-45		1
PS/2		1
DC-in		1
Microphone		1
Headphone		1
Power on switch		1
Kensington Lock		1
Camera	Built-in ConfCamera (1,3 megapixle VGA Camera)	
Modem on board		
56K V.92 modem MDC1.5		1
LAN on board		
built-in 10/100/1000 Mbps Marvell 88E8055		x
Wireless Technologies (WLAN)		
Import and usage according to country-specific regulations.		
3 Dual band WLAN antennas, 2 UMTS antennas		
Intel® Pro Wireless 4965 a/g/n		optional
Atheros Minicard b/g 802.11 b/g		optional
WiFi certified		x
Integrated UMTS/HSUPA, also supported are GPRS and EDGE or higher	Optional (downlink 7.2, uplink 2.0)	
Bluetooth		
Bluetooth V2.0		optional
Audio		
Stereo speakers		x
Sound chip		RealTek ALC262
Internal microphone		2
Keyboard and pointing device		
Keyboard	Spill proof keyboard, 85 keys, 19mm pitch, 3mm key stroke	
Touchpad	with two mouse buttons, scroll via fingerprint sensor	
Fingerprint sensor		x
Launch Keys		x
Application Buttons		x
Lock workstation Button		x
Mobility Center Button		x
Eco Button		x
Recovery Button		x
Status LED		x
Graphics		
Intel® X3100 integrated graphics		x
Direct X9		x
Direct X10		x (Q4/2007)
Pixelshader 3.0		x
Pixelshader 4.0		x (Q4/2007)

DualView (Windows XP & Windows Vista)		x
Display 13.3-inch TFT WXGA /1280 x 800 pixel, glare display Max. resolution for external displays		x 1920 x 1200 / true color / 60 Hz (tbd.)
Hard disk drives (internal) * S.M.A.R.T. ShockSensor for HDD shock protection 80 GB S-ATA 150 (5400 rpm) 120 GB S-ATA 150 (5400 rpm) 160 GB S-ATA 150 (5400 rpm)** * 1 Gbyte equals one billion bytes, when referring to hard disk drive capacity; accessible capacity may vary, also depending on used software and tool. ** for projects only		x x x x x x
Modular Drives DVD super-multi drive incl. RAM More information in specific Data Sheet: http://www.fujitsu-siemens.com/optical_drives/		x
Manageability Please refer to http://www.fujitsu-siemens.com/solutions/business_solutions/manageability/featurefinder.html		
Supported Standard WMI / CIM / WBEM PXE BootP		x x made4you
Security Physical security Kensington Lock support		x
System Security Boot sector virus protection Trusted Platform module 1.2 Symantec Norton Internet Security		- optional x
User Security User and supervisor BIOS password SystemLock BIOS SmartCard security Hard disk password Integrated Fingerprint Sensor Integrated SmartCard controller in PC Card with system lock support SmartCase Logon+ incl. Fingerprint Software		x x x x x x
Power supply 1st Li-Ion battery 6 cell 5200mAH (53.3 Wh) 2nd Li-Ion battery 6 cell 2300mAh (24.8Wh) (Option) First battery * (Mobile Mark 2005) [up to] First + Second battery * (Mobile Mark 2005) AC adapter 19V/80W Adapter Rated voltage (AC input) 100 - 240 V Rated frequency 50 - 60 Hz DC output 19 V, 4.22		optional 8 h 11.4 h x
Operating temperatures Relative humidity (non-condensing) Ambient temperature		20% - 85% (running) 5° - 35° C
Dimensions / Weight Dimensions (H x W x D) Weight*		314 x 234 x 22.7 - 31.5 mm 1,75 kg
* Weight may vary depending on actual configuration		
Certificates CE Marking CE according to EU Directives 89/336/EEC (EMC) 73/23/EEC (Product safety) CE according to 99/5/EEC (R&TTE) CE! (Wireless) CE (Emission/Immunity) R&TTE FCC GS (German ergonomic approval) UL/cUL CB Generic Report CB (Safety) RoHS WHQL TBR21 Energy Star WiFi certified		x x x x (with integrated WLAN) x x - tbd x x x x x x x x x - x
Operating System Microsoft Windows XP Professional Microsoft Windows Vista™ Microsoft Windows Vista® Business/ Microsoft Windows XP® Professional TwinLoad		driver support x x
Software (compatibility / preinstalled) Adobe Acrobat Reader Application panel tool Camera Windows Vista recovery media Driver and Utility DVD (DUDVD) Eco Power Saving Utility Easy Guide on-line user documentation		x x x optional (extra order number) optional (extra order number S26361 F2007 E903) x x

Nero Essentials Norton Internet Security (incl. Firewall) on DUDVD for Microsoft Windows XP SmartCase Logon+ Toshiba Bluetooth Stack UMTS watcher DVD playback software	x x x x optional with UMTS optional
Accessories (order number) AC-adapter Case Port Replicator Battery Modem adapter set 1: D, UK Modem adapter set 2: SW, NO, FI, DK Modem adapter set 3: CH, A, B, NL, F, I, E, POR http://www.fujitsu-siemens.com/accessories/	S26391-F408-L300 S26391-F119-L57 S26391-408-L100 1st: S26391-F405-L820 2nd: S26391-F405-L821 S26391-F3145-L10 S26391-F3145-L20 S26391-F3145-L30
Spare part availability	5 years